



# Scanners

Nired / Handheld

Handheld scanners make work easier with fast, accurate barcode scanning in retail, industrial, manufacturing, and enterprise environments. CipherLab's reliable and rugged handheld, wired scanners are designed to help accelerate productivity while minimizing total cost of ownership.

## Scanners

Wired / Handheld



Comfortable, powerful, hard-working scanners delivering outstanding service and value

Wherever handheld scanners are used—on the shop floor, at the checkout counter, in the manufacturing line, or in the documentation center—they must be comfortable and safe for the user, stand up to tough environments, be cost-effective to operate, and deliver undeniably accurate scans all day long.

CipherLab designs and manufactures the industry's top handheld scanners to provide outstanding, long-lasting service for workers and deliver a high return on investment (ROI). Reliability, user comfort, rugged construction, and low power consumption (an average 50 percent lower than competitors' devices) make CipherLab scanners the ideal choice for long-lasting value in any industry.



When it comes to reading a variety of symbologies and printed materials, the CipherLab 1000 and 1090+ CCD Scanners are ideal for consistently accurate data capture in any environment. Contact scanners eliminate misreading clustered or poorly printed bar codes. Smart ergonomic design with a sturdy thermoplastic polyurethane (TPU) rubber boot make them easy to use and rugged. Auto-discrimination of the barcode type and a CCD imager instead of a laser make them accurate, reliable scanners, with no moving parts to break down. Low power consumption helps minimize TCO and makes these scanners ideal choices for close scanning, even of wider barcodes (up to 90 mm with the 1090+).

### 1100/1105

For fast scanning of multiple symbologies, the CipherLab 1100/1105 Retail Linear Imaging Scanners are ideal to boost productivity with low cost of ownership. These scanners automatically sense symbology type and read barcodes up to 20 cm/7.9 in. away, making them easy-to-use, versatile tools. Built with no moving parts and using rugged double-injection molded TPU, the 1100/1105 scanners withstand multiple 2-meter/6.5-foot drops onto concrete, providing long-lasting service with low total cost of ownership.

### 1200

Ideal for retail applications, the CipherLab 1200 Laser Scanner quickly and accurately reads barcodes up to 64 cm/2 ft. away, allowing you to work smarter and faster. Small size, ergonomic design, and light weight make the 1200 scanner easy and comfortable to use all day long.







## ScanManager<sup>™</sup>—PC software to custom-configure your scanner to any environment

CipherLab ScanManager<sup>™</sup> software provides comprehensive tools to configure your scanner, such as enabling and disabling auto-sense mode, choosing edit format and symbology types, plus more. With ScanManager software, you can easily customize the scanner to your environment. ScanManager software for PC is included with all CipherLab scanners.

#### CipherLab—the scanner pioneer

#### LEADER IN THE INDUSTRY

CipherLab leads the industry with high-quality, rugged scanners that are designed to meet the specific needs of users in a wide range of environments. We acquired our leadership position through more than fifteen years of designing and manufacturing scanners, from our first CCD barcode scanner released in 1991 to our most recent announcements of powerful, versatile handheld scanners.

#### TAKING CARE OF OUR CUSTOMERS

Our customers trust the experience we've gained from working with many different industries and providing them scanning solutions to help boost productivity with low TCO. Our scanners can be found in retail, medical, transportation, manufacturing, and financial sectors. That's why we understand the needs of both the industries scanners are used in and the people who handle them all day long. We back our reputation for quality and reliability with a 5-year warranty on our non-laser handheld scanners.

#### **EXTENSIVE RESEARCH AND DEVELOPMENT**

Innovative engineering and design is supported with extensive research and development in optics, electronics, and communications technology. Our R&D engineers ensure operating satisfaction from proof-of-concept to production-line products.

#### INTERNATIONALLY RECOGNIZED QUALITY

Our commitment to the highest manufacturing quality is recognized around the world by users and businesses that depend on the daily performance of our scanners. We operate under the ISO 9001 quality standards and ISO 14000 environmental standards certified by international organizations. You can trust CipherLab scanners to deliver dependable operation with a low TCO and high ROI. Our products are recognized around the world for their work and business value:

- ▶ RANKED IN TOP FIVE BY RESELLERS In 2006, Vertical Systems Reseller, a leading United States AIDC magazine, rated CipherLab among the top five scanner manufacturers.
- RATED IN TOP THREE WORLDWIDE In a Venture Development Corporation 2006 survey, end users ranked CipherLab in the top three best handheld scanners.
- ▶ CIPHERLAB SCANNERS USED BY MILLIONS WORLDWIDE CipherLab scanners lead worldwide sales with a reputation for quality and reliability.







CIPHERLAB PRODUCTS ARE
VALUED WORLDWIDE FOR
ENGINEERING EXCELLENCE.
OUR HANDHELD SCANNERS
ARE ANOTHER EXAMPLE OF
TECHNICAL INNOVATION AND
QUALITY VALUE FOR TODAY'S
AIDC SOLUTIONS.

## Scanners

Wired / Handheld



Optical sensor   2048 pixels   2048 pixels   3648 pixels   Laser						
Optical sensor   2048 pixels   2048 pixels   3648 pixels   Laser scanner   Light source   Red LED (660 nm)   Red LED (650 nm)   Red LED (630 nm)   Visible laser diode (65)   Resolution   3 mil   4 mil   4 mil   3 mil   4 mil   4 mil   3 mil   4 mil   4 mil   5 marched resolution   0 to 0.4 in.   0 to 5 cm   2.5 to 20 cm   1 to 63 cm   2 mil to 70   1			1000 K/R/U	1090+	1100	1200
Light source	Performance	Category	CCD contact scanner		Linear imaging scanner	Laser scanner
Resolution   3 mil   4 mil   3 mil   4 mil   2 mil   4 mil		Optical sensor	2048 pixels	2048 pixels	3648 pixels	Laser
Depth of field (depends on barcede resolution)   O to 1 cm   O to 5 cm   0 to 2 in.   1 to 7.9 in.   O.4 to 25 in.   Scanning angle   Pitch ± 70°   Pitch ± 70°   Pitch ± 70°   Skew ± 40°   Skew ± 70°   Skew ± 70°   Skew ± 70°   Skew ± 32.		Light source	Red LED (660 nm)	Red LED (650 nm)	Red LED (630 nm)	Visible laser diode (650 ±15 nm)
(depends on barcode resolution)   0 to 0.4 in.   0 to 2 in.   1 to 7.9 in.   0.4 to 25 in.		Resolution	3 mil	4 mil	3 mil	4 mil
PCS						1 to 63 cm 0.4 to 25 in.
Scan rate		Scanning angle				Pitch ± 70° Skew ± 32.5°
Autosense mode		PCS	Minimum 30%			
Interfaces supported   RS232 / Keyboard wedge / Wand emulation (except 1000) / USB HID / USB Virtual Com / IBM 46		Scan rate	100 scans/second			35 ± 5 scans/second
Barcodes supported   Codabar, Code 39, Code 128, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Pharmacodes, Plessey, RSS14, Telepen, UPC/EAN, and more		Autosense mode	n/a Yes		Yes	n/a
Programmable features		Interfaces supported	RS232 / Keyboard wedge / Wand emulation (except 1000) / USB HID / USB Virtual Com / IBM 4683/4694			
Language support   US and UK English/French/Italian / Belgian/Norwegian/Swedish/Spanish/Portuguese/Gerr		Barcodes supported	Codabar, Code 39, Code 93, Code 128, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Pharmacodes, Plessey, RSS14, Telepen, UPC/EAN, and more			
Physical   Weight   265 g / 9.3 oz. (w/cable)   148 g / 5.2 oz.   165 g / 5.8 oz.   190 g / 6.7		Programmable features				
Color   Ivory   Light grey or dark grey		Language support	US and UK English/French/Italian /Belgian/Norwegian/Swedish/Spanish/Portuguese/German			
Switch   Rubber switch   Micro switch	Physical	Weight	265 g / 9.3 oz. (w/cable)	148 g / 5.2 oz.	165 g / 5.8 oz.	190 g / 6.7 oz.
Power Consumption   15 mA / 60 to 80 mA / 85 to 110 mA   15 mA / 60 mA / 90 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 60 mA / 90 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA		Color	lvory		Light grey or dark grey	
Power Consumption   15 mA / 60 to 80 mA / 85 to 110 mA   15 mA / 60 mA / 90 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 60 mA / 90 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 60 mA / 90 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 180 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA   15 mA / 80 mA / 160 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 85 to 110 mA / 180 mA / 160 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / 180		Switch	Rubber switch		Micro switch	
Standby / Scanning / Maximum   85 to 110 mA   15 mA / 60 mA / 90 mA   15 mA / 80 mA / 160 mA   15 mA / 170 mA / mA	Electrical	Voltage	+5 V ±5%	+5 V ±5%	+5 V ±10%	+5 V ±5%
Environment  Storage temperature				15 mA / 60 mA / 90 mA	15 mA / 80 mA / 160 mA	15 mA / 170 mA / 250 mA
Storage temperature  -20°C to 60°C / -4°F to 140°F  Operating/storage humidity  Non-condensing 10% to 90% / 5% to 95%  Impact resistance Multiple drops onto concrete  1.0 m (3.3 ft.) drops  2 m (6.6 ft.) drops  1.2 m (4 ft.) drops  Electrostatic discharge  Conforms to ±15 kV air discharge and ±8 kV contact discharge  EMC regulation  FCC / CE / C-tick / BSMI / MIC  FCC / CE / C-tick / BSMI / MIC		Operating temperature	0°C to 50°C / 32°F to 122°F			0°C to 40°C / 32°F to 104°F
Impact resistance Multiple drops onto concrete  Electrostatic discharge  EMC regulation  EMC regulation  Conforms to ±15 kV air discharge and ±8 kV contact discharge  FCC / CE / C-tick / BSMI / MIC  FCC / CE / C-tick / BSMI / MIC  FCC / CE / C-tick / BSMI / MIC		Storage temperature	-20°C to 60°C / -4°F to 140°F			-40°C to 60°C / -40°F to 140°F
Multiple drops onto concrete    Conforms to ±15 kV air discharge and ±8 kV contact discharge		Operating/storage humidity	Non-condensing 10% to 90% / 5% to 95%			
EMC regulation FCC / CE / C-tick / BSMI FCC / CE / C-tick / BSMI / MIC FCC / CE / C-tick / BSMI / MIC			1.0 m (3.3 ft.) drops		2 m (6.6 ft.) drops	1.2 m (4 ft.) drops
BSMI / MIC BSMI BSMI / MIC BSMI BSMI / MIC BSMI BSMI / MIC		Electrostatic discharge	Conforms to ±15 kV air discharge and ±8 kV contact discharge			harge
Configuration Setup options include Windows*-based ScanManager software (included), by direct connection or printing out barcode setting		EMC regulation	FCC / CE / C-tick / BSMI		FCC / CE / C-tick / BSMI	FCC / CE / C-tick / BSMI / MIC
	Configuration	Setup options include Windows*-based ScanManager software (included), by direct connection or printing out barcode settings				
Accessories Includes attached cable Detachable cable, desk/wall mount included with 1100/1200. Optional autosense stand for 1100.	Accessories		I Includes attached cable			
Warranty 5 year 1 year	Warranty		5 year 1 year			

ACCESSORIES



Auto Sense Stand



Can be used on tabletop or wall mounted



©2008 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved.



www.cipherlab.com